



Technical Data Sheet

Product	Type
----------------	-------------

SulfoGel™ 181

Metal Protection
High Solids thixotropic overbased calcium sulfonate

Application

SulfoGel 181 is a high-solids, very-low VOC, thixotropic overbased calcium sulfonate in an oil carrier. It is an ideal starting material for formulating long-term, permanent rust preventives for automotive underbodies, wire rope lubricants, shipout casting, ballast tank coatings, and seam sealants.

Typical Properties


Test	Typical
Appearance	Tan Viscous fluid
Pounds per gallon @25° C	8.5
Total base number, mg KOH/g	181
Brookfield RTV viscosity @ 25° C	90,000
Non-volatile, wt. %	>97
Water, wt. %	~1.0

Benefits

- Excellent Wetting and water displacing properties
- Resists Corrosion of steel
- Good boundary lubricant for forming operations
- Low VOC starting material for long term rust preventive coatings

Storage and Handling

Recommended Max Long Term Storage Temperature	Ambient
Flash Point	>175° C



DISCLAIMER: To the best of our knowledge, the information and recommendations contained herein are accurate. However, this information and recommendations are furnished without any warranty, representation or license of any kind. Users of our products are encouraged to run their own tests to ensure product fitness for their applications. Furthermore, users assume sole liability for any patent infringement that occurs by reason of following our recommendations or using the information given