



## Technical Data Sheet

Product	Type
---------	------

### SulfoGel™ 280

### Metal Protection

High solids thixotropic overbased calcium sulfonate

### Application

SulfoGel 280 is a high-solids, very-low VOC, thixotropic overbased calcium sulfonate in an oil carrier. SulfoGel 280 is an economical calcium grease base. It is also an ideal starting material for formulating long-term, permanent rust preventives for automotive underbodies, wire rope lubricants, shipout casting, ballast tank coatings, and seam sealants.

### Typical Properties


Test	Typical
Pounds per gallon @25° C	8.8
Brookfield RTV viscosity @ 25° C	110,000
Total base number, mg KOH/g	270
Non-volatile, wt. %	98
Water, wt. %	0.5

### Benefits

- Excellent Wetting and water displacing properties
- Resists Corrosion of steel
- Good boundary lubricant for forming operations
- Low VOC starting material for long term rust preventive coatings

### Storage and Handling

Recommended Max Long Term Storage Temperature	Ambient
Flash Point	>175° C



**LOCKHART**

Technologies for  
Better Surface Protection

**Lockhart Chemical Company**  
4302 James P Cole Boulevard Flint, MI 48505  
Phone: 1-810-789-8330 Fax: 1-810-789-3266  
[www.lockhartchem.com](http://www.lockhartchem.com)  
[email: customerservice@lockhartchem.com](mailto:customerservice@lockhartchem.com)

**DISCLAIMER:** To the best of our knowledge, the information and recommendations contained herein are accurate. However, this information and recommendations are furnished without any warranty, representation or license of any kind. Users of our products are encouraged to run their own tests to ensure product fitness for their applications. Furthermore, users assume sole liability for any patent infringement that occurs by reason of following our recommendations or using the information given