



Technical Data Sheet

Product	Type
---------	------

SulfoGel™ 760

Metal Protection

Semi-Finished thixotropic calcium sulfonate coating

Application

SulfoGel 760 is a low VOC semi-finished coatings products that can be used directly or further formulated.

SulfoGel 760 is a thixotropic overbased calcium sulfonate in low aromatic mineral spirits and is compatible with most hydrocarbon materials such as waxes, petrolatums, oils and resins.

SulfoGel 760 applications include solvent born rust preventives, vehicle undercoatings, cavity waxes, temporary parts protectorants and frame coatings

Typical Properties

Test	Typical
Pounds per gallon At 25° C	8.8
Brookfield viscosity @ 25° C	70,000
Non-volatile, wt.%	62
Total base number, mg KOH/g	250
Water wt. %	1.0

Benefits

- Exceptional corrosion protection in salt environments
- Highly resistant to chloride induced corrosion
- Excellent surface wetting agent
- Provide excellent rheology and anti-sag properties

Storage and Handling

Recommended Storage Temperature	10-30° C
Flash Point	>61 ° C



LOCKHART

Technologies for
Better Surface Protection

Lockhart Chemical Company

4302 James P Cole Boulevard Flint, MI 48505

Phone: 1-810-789-8330 Fax: 1-810-789-3266

www.lockhartchem.com email: customerservice@lockhartchem.com

DISCLAIMER: To the best of our knowledge, the information and recommendations contained herein are accurate. However, this information and recommendations are furnished without any warranty, representation or license of any kind. Users of our products are encouraged to run their own tests to ensure product fitness for their applications. Furthermore, users assume sole liability for any patent infringement that occurs by reason of following our recommendations or using the information given